



COLOTEC QUÍMICA S.L.

TECHNICAL SHEET

Fecha: 09/05/2024 .

This file replaces sheet with date

IDENTIFICATION

Reference:

SLIP AV/E-5681B

Array:

PLASTIC ADITIVE

RECOMMENDED MATERIALS

<input type="radio"/>	LD-PE:	<input type="radio"/>	PS	<input type="radio"/>	ABS	<input type="radio"/>	PC	<input type="radio"/>	PVC rígido
<input type="radio"/>	HD-PE	<input type="radio"/>	SB	<input type="radio"/>	POM	<input type="radio"/>	PMMA	<input type="radio"/>	PVC Plástico
<input type="radio"/>	PP	<input type="radio"/>	BDS	<input type="radio"/>	PA	<input type="radio"/>	EVA	<input type="radio"/>	Caucho

Legend: ☐ Not recommended ☒ Partially recommended ☒ Recommended

PHYSICAL & CHEMICAL FORM

PROPERTY NO.1

It is insoluble in water

PROPERTY NO.2

Melting point: 90-120°C.

PROPERTY NO.3

Thermal stability: 240 °C.

PROPERTY NO.4

It produces a slip and anti-blocking effect in film sheets.

PROPERTY NO.5

It acts as a separating and antistatic agent in plastic resins.

PROPERTY NO.6

It acts as a lubricant, which improves the fluidity of the material.

INFORMATION ABOUT THE COMPOSITION

LEGISLATION

ADVANTAGES OF USING MASTERBATCH

OTHER INFORMATION

IMPORTANT REMARKS